

Report no :	bsi-1784-97
Report Title :	Protection Test
Report Date :	07.03.2020



Product / Code	iNerra
Test Method No	DT-LVD-21/R2
Environmental Conditions	23.4°C, % 50 RH
Test Duration	3min
Related Standard	TS 3033 EN 60529:1997 TS EN 60529/A2:2014-02

TEST CONDITIONS AND RESULTS

Test specification The conditions to be observed are as follows:
Internal diameter of the nozzle : 6.3mm;
Delivery rate: 12.5 l/min $\pm$ 5 %;
Water pressure: To be adjusted to achieve the specified delivery rate;
Core of the substantial stream: Circle of approximately 40mm diameter at 2.5mm distance from nozzle;
Test duration per square meter of enclosure surface area likely to be sprayed: 1min;
Minimum test duration: 3min;
Distance from nozzle to enclosure surface: between 2.5m and 3m.

Test Result:

There have to be no slew of water that may obstruct impeccable working or unsecure the EUT.

As a result of the applied forces, impact resistance has been determined. (IK09)

Tested by : Ali KIZGIN Date : 07.03.2020	Approved by : Serdar ERCIYES Date : 07.03.2020 Signature :  
---	---

Report no :	bsi-1784-97
Report Title :	Protection Test
Report Date :	07.03.2020

