



Creative Linear Pixel

Encapsulated linear pixel luminaires designed to highlight the exceptional character of large-scale architectural structures and spaces such as skyscrapers, stadiums, theme parks, bridges, airports, and shopping malls. BS Line PX video pixel linear engineered to provide powerful pixel mapping and media effects. It is a versatile tool for linear and radial installations where high-visibility and a very flexible setup are essential.

Architectural LED linear range inspires architects, designers and system integrators with its exceptional quality, homogeneous light output and remarkable creativity.

Sleek and High-Performance


Efficient design luminaire that features tremendous modularity and ease of use. BS Line PX is made of anodized aluminum, resulting in a form with simplicity matches its function. Available in different lengths with multiple accessories like opal lenses, brackets, and extension cables.

Exceptional performance and compact dot-free, homogeneous light-emitting surface with polyurethane encapsulation make it more resistant to salt water, UV light and solvents.


Functional and Easy to Install

Thanks to its ultra-flat profile, it blends perfectly into any architectural environment and is characterized by its functionality, versatility and exceptional appearance. By integrating exceptional pixel mapping features, it allows to create 3D elements and abstract images with solid artistic impact.



The watertight connector system ensures easy, fast and secure installation. The robust luminaire fits seamlessly into the architecture.



BS Line PX					
Codes	Power	Colour Temperature	A (mm)	B (mm)	L (mm)
AR9732102 PX	10W/m Full On	RGB	28	65	300
AR9732104 PX	10W/m Full On	RGB	28	65	600
AR9732106 PX	10W/m Full On	RGB	28	65	900
AR9732108 PX	10W/m Full On	RGB	28	65	1200
AR9732110 PX	10W/m Full On	RGB	28	65	1500



Diffused Beam



Technical Features
Corrosion resistant extruded anodized aluminium housing (EN AW-6060) with stainless steel screws (A4 grade) and epoxy resin. Operates with a remote driver. Includes waterproof connectors and mounting bracket.
High efficiency 42 LEDs Per Meter with in LED MacAdam Step 3
Nominal Voltage 24V DC
Operating Temperature -40°C / +55°C
Control Systems 1-10V DIM, DMX / RDM, DALI Interface (External)
Protection Class IP67
Impact Resistance IK09
Insulation Class III
Complies with EN60598 and relevant standards.

BS Line PX



For detailed information about the BS Line PX