

## Key Features

BS Dot pixel fixture with diffused version provides special video effects with maximum brightness. Enables endless layout of patterns, graphics display and offers customizable solutions pixel mapping with DMX 512 and RDM protocol.

High-performance media LED Dot for large locations allows for long fixture runs with variable pixel pitches for flexible designs. An inventive instrument for video display setups. Perfect viewing without pixel gap or shade in the connection points.

Compact LED module providing ultra-bright spot light output. BS Dot is the ideal solution for displaying video files, stunning visual effects and graphic patterns.


Designed to last in extremely harsh environments.



## Key Data

<b>Product Type</b>	Dynamic White
<b>LED Type</b>	High efficiency 5050 (AMB-WW-CW) SMD LED, available in 2700K, 3000K, 4000K, 5000K, 6500K CCT tolerance within a 3-step MacAdams ellipse and LM80 compliant.
<b>Nominal Voltage</b>	24V DC (Standard) / 48V DC (Optional)
<b>Color Rendering Index</b>	CRI ≥ 80 standard and CRI ≥ 90 on request.
<b>Light Distribution</b>	120°
<b>Materials</b>	UV-Protected ABS Body
<b>Body Colors</b>	9016 White, 9005 Black, 9006 Grey
<b>Diffuser</b>	UV-Protected Polycarbonate Diffuser
<b>LED Life Time</b>	L90 - B50 > 60,000h
<b>Operating Temperature</b>	-30°C / +65°C
<b>Pixel Pitch</b>	12.5 cm / 25 cm / 50 cm (Standart) Variable pixel pitch
<b>Dots Per String</b>	1 (1.5W/ 60 lm), 10 (15W/ 600 lm), 25 (37.5W/ 1500 lm), 50 (75W/3000 lm), 100 (150W/6000 lm)
<b>Number of LEDs</b>	6 LED
<b>Control</b>	SPI (Standard) / DMX512 (Optional)
<b>Protection Class</b>	IP68
<b>Impact Resistance</b>	IK10
<b>Insulation Class</b>	Class III
<b>Conformity</b>	CE, RoHS


Technical Drawing



Information

PRODUCT	POWER CONSUMPTION	LUMEN OUTPUT (lm)	COLOUR TEMPERATURE
AR642204 DOME	1,5W-150W	60 lm-6000 lm	White CCT 2700-6500K

Light Distribution Curve



Diffused Beam