

## Key Features

iAxis RGB-RGBW Recessed luminaire is suitable for a wide range of wall washing, accent, surface grazing and indirect lighting applications in architectural, hospitality and retail environments, it has multiple customization options to illuminate interior walls, exterior facades and unique architectural details.

Driveover 4000 Kg at max 40 Km/h.

The luminaire is available with frame and frameless versions.

Designed to last in extremely harsh environments.


RGBW, DMX or DALI controllable, easy to install with the integrated universal power supply and connect via combined power and data connectors.



## Key Data

<b>LED Type</b>	High efficiency LEDs, available in 2700K, 3000K, 4000K, 5000K, 6500K CCT tolerance within a 3-step MacAdams ellipse and LM80 compliant. Custom LED color combinations available.
<b>Nominal Voltage</b>	220V-240V AC, 50/60Hz
<b>Color Rendering Index</b>	CRI ≥ 80 standard and CRI ≥ 90 on request.
<b>Colour Temperature</b>	16.7 Million additive RGB colors.
<b>Optics</b>	Standard: 8° / 12° / 25° / 30° / 45° / 60° / 90° / 18°x38° / 10°x60° / 25°x50° Asymmetrical Linear Wallwash. Custom optics upon request.
<b>Materials</b>	Corrosion resistant extruded anodized aluminium housing (EN AW-6060) with stainless steel screws (A4 grade) and silicone rubber gaskets. Power unit is built in. End-to-end connection via power connectors. Includes recessing box.
<b>Optional Coating</b>	Marine grade.
<b>Options</b>	Aluminium frame with aluminium recessed box.
<b>Diffuser</b>	High impact and heat resistant polycarbonate with UV protection.
<b>LED Life Time</b>	L80 B10 70.000h Ta 25°C L80 B10 50.000h Ta 40°C
<b>Operating Temperature</b>	-40°C / +55°C
<b>Power Factor</b>	>0.95
<b>Control Systems</b>	DMX / RDM, DALI Interface.
<b>Protection Class</b>	IP67
<b>Impact Resistance</b>	IK10
<b>Load Rating</b>	40 kN
<b>Insulation Class</b>	Class I
<b>Installation</b>	20-30 cm drainage gravel for water evacuation.
<b>Conformity</b>	Complies with European Standards EN 60598 and CE certified.

### Technical Drawing



### Information

CODE	LENGTH Frameless (mm)	LENGTH With Frame (mm)	PITCH (mm)	LED QTY	POWER CONSUMPTION 350mA	POWER CONSUMPTION 500mA	LUMEN OUTPUT (lm) 350mA	LUMEN OUTPUT (lm) 500mA
AR8122264 RGBW	920	967	37	24	24W	36W	1680	2520

### Light Distribution Curve



### Accessories



**Honeycomb Louvre**  
Code: HC3001



**Aluminium Frame**  
Code: AF5001



**IP68 Plug Power Connector Set (Two pieces)**  
Code: CON1202