



Light Columns

iLara is ideal for lighting up modern and architectural squares or walkways, it has 4 vertical arms at each corner, which give it a thin and slender silhouette.

Architectural LED lighting column range inspires architects, designers and system integrators with its exceptional quality, a variety of beam angles and remarkable creativity.

Modular and Flexible


The iLara collection is characterized by clean, pure and minimal lines that soberly articulate in space, while responding to a modular and flexible design.

The luminaire with stylized appearance and with improvements in installation, maintenance and service life offers a wide variety of light distributions that ensure effective values, visual comfort and light output for pedestrian areas without light pollution. The possibility to use various photometric distribution with optional mounting heights allows designers to illuminate differing urban spaces with original system configurations.

Modern Design and Easy to Install

Modern design adapted to the requirements and conditions of the client and project. The luminaire is equipped with an integral power supply unit, is optionally available with DALI control or in the user-friendly On-Off version. The columns can be illuminated from the inside by an independent light source, so that even at night the column is an interesting feature in the landscape.


The product is supplied pre-wired, permitting simple, rapid and safe installation.




iLara					
Codes	Power	Colour Temperature	A (mm)	H (mm)	F (mm)
LB1352	38W	3000K / 4000K	220	3000	300
LB1354	54W	3000K / 4000K	220	4500	300




40 degree



60 degree




Available in Black colour




90 degree




IESNA Type II



Available in Corten colour




IESNA Type III (medium)




IESNA Type IV



Available in Silver colour



IESNA Type V (square)



Pedestrian Walkways



Technical Features

Corrosion resistant double layer polyester powder coated paint finish die cast aluminium housing, aluminium extruded column (EN AW-6060) with stainless steel screws (A4 grade) and silicone gaskets. Power unit is built in. Available in anthracite gray as a standard finish or any desired RAL colour.

LED MacAdam Step 3

Nominal Voltage 220V-240V AC, 50/60Hz

Operating Temperature -40°C / +55°C

Control Systems 1-10V DIM, DALI Interface

Protection Class IP65

Impact Resistance IK08

Insulation Class I

Complies with EN60598 and relevant standards.

iLara



For detailed information about the iLara